

For Industrial Use Only

KEEP OUT OF REACH OF CHILDREN
READ SAFETY INSTRUCTIONS BEFORE USE



YASH ENTERPRISES



BRITTO 2

*Pickling & Passivation Chemicals
for SS 304 and 316 L Fabrications*

PICKLING GEL

(Confirms To The Requirement Of Astm-a-380 And Is : 10117) **UN 2922 CORROSIVE LIQUID TOXIC**

Contents (Approx): Hydrofluoric Acid 45 Gpl, Nitric Acid 285 Gpl : organo Gums, Thixotropic agent W&D Agents, Fume Suppressants, oxidizing Chemical

BRITTOSS RANG is used to remove the black oxide marks or burn marks or burn scale left after welding of SS 304 & 316L Chemical process plants & equipments Fabrication

DIRECTION FOR USE : always use Britoss in OPEN & VENTILATED areas.

- A.** Brush weld area with stainless, steel Brush to remove loose foreign matter.
B. Apply BRITTOSS with brush or acid resistant pump & spray evenly on entire surface area
C. After 15-45 minutes, rise off with water under high pressure jet. Application time will depend upon Grade, Thickness & type of welding of stainless steel.

- NOTE: 1.** wear all safety gear , Rubber Apron . avoid spillage or splashes.
2. Replace lid on the container and store upright in cool dry area, away from direct sun and heat. Do not apply on hot surface.

WARNING: BRITTOSS range is corrosive and an irritant. Avoid Contact with skin and avoid breathing its vapour. Contact with eyes. even for a short period can cause blindness. Wash with plenty of running water in case of spillage or contact with skin.

FRIST AID : If Poisoning Occurs, Contact A Doctor

UN 2922	CLASS 8	SUB RISK 6.11	PG II	HAZ. CHEM 2X
------------	------------	------------------	----------	-----------------



Manufactured & Marketed By :
YESH ENTERPRISES

BATCH NO :
MFG DATE :
EXP DATE :
QTY :
MRP :

User Frinendly RoHS Compliant
Water Washable Acidic Formulation
YESH ENTERPRISES
Collbration Japinies
rahul_rc8@rediffmail.com



For Industrial Use Only

KEEP OUT OF REACH OF CHILDREN
READ SAFETY INSTRUCTIONS BEFORE USE



YASH ENTERPRISES



BRITTO 2

*Pickling & Passivation Chemicals
for SS 304 and 316 L Fabrications*

PICKLING GEL

(Confirms To The Requirement Of Astm-a-380 And Is : 10117) **UN 2922 CORROSIVE LIQUID TOXIC**

Contents (Approx): Hydrofluoric Acid 45 Gpl, Nitric Acid 285 Gpl : organo Gums, Thixotropic agent W&D Agents, Fume Suppressants, oxidizing Chemical

BRITTOSS RANG is used to remove the black oxide marks or burn marks or burn scale left after welding of SS 304 & 316L Chemical process plants & equipments Fabrication

DIRECTION FOR USE : always use Britoss in OPEN & VENTILATED areas.

- A.** Brush weld area with stainless, steel Brush to remove loose foreign matter.
B. Apply BRITTOSS with brush or acid resistant pump & spray evenly on entire surface area
C. After 15-45 minutes, rise off with water under high pressure jet. Application time will depend upon Grade, Thickness & type of welding of stainless steel.

- NOTE: 1.** wear all safety gear , Rubber Apron . avoid spillage or splashes.
2. Replace lid on the container and store upright in cool dry area, away from direct sun and heat. Do not apply on hot surface.

WARNING: BRITTOSS range is corrosive and an irritant. Avoid Contact with skin and avoid breathing its vapour. Contact with eyes. even for a short period can cause blindness. Wash with plenty of running water in case of spillage or contact with skin.

FRIST AID : If Poisoning Occurs, Contact A Doctor

UN 2922	CLASS 8	SUB RISK 6.11	PG II	HAZ. CHEM 2X
------------	------------	------------------	----------	-----------------



Manufactured & Marketed By :
YESH ENTERPRISES

BATCH NO :
MFG DATE :
EXP DATE :
QTY :
MRP :

User Frinendly RoHS Compliant
Water Washable Acidic Formulation
YESH ENTERPRISES
Collbration Japinies
rahul_rc8@rediffmail.com



For Industrial Use Only

KEEP OUT OF REACH OF CHILDREN
READ SAFETY INSTRUCTIONS BEFORE USE



YASH ENTERPRISES



BRITTO 2

*Pickling & Passivation Chemicals
for SS 304 and 316 L Fabrications*

PICKLING GEL

(Confirms To The Requirement Of Astm-a-380 And Is : 10117) **UN 2922 CORROSIVE LIQUID TOXIC**

Contents (Approx): Hydrofluoric Acid 45 Gpl, Nitric Acid 285 Gpl : organo Gums, Thixotropic agent W&D Agents, Fume Suppressants, oxidizing Chemical

BRITTOSS RANG is used to remove the black oxide marks or burn marks or burn scale left after welding of SS 304 & 316L Chemical process plants & equipments Fabrication

DIRECTION FOR USE : always use Britoss in OPEN & VENTILATED areas.

- A.** Brush weld area with stainless, steel Brush to remove loose foreign matter.
B. Apply BRITTOSS with brush or acid resistant pump & spray evenly on entire surface area
C. After 15-45 minutes, rise off with water under high pressure jet. Application time will depend upon Grade, Thickness & type of welding of stainless steel.

- NOTE: 1.** wear all safety gear , Rubber Apron . avoid spillage or splashes.
2. Replace lid on the container and store upright in cool dry area, away from direct sun and heat. Do not apply on hot surface.

WARNING: BRITTOSS range is corrosive and an irritant. Avoid Contact with skin and avoid breathing its vapour. Contact with eyes. even for a short period can cause blindness. Wash with plenty of running water in case of spillage or contact with skin.

FRIST AID : If Poisoning Occurs, Contact A Doctor

UN 2922	CLASS 8	SUB RISK 6.11	PG II	HAZ. CHEM 2X
------------	------------	------------------	----------	-----------------



Manufactured & Marketed By :
YESH ENTERPRISES

BATCH NO :
MFG DATE :
EXP DATE :
QTY :
MRP :

User Frinendly RoHS Compliant
Water Washable Acidic Formulation
YESH ENTERPRISES
Collbration Japinies
rahul_rc8@rediffmail.com

